

SAFETY DATA SHEET
FABSIL GOLD

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME FABSIL GOLD
 PRODUCT NO. GRF
 SUPPLIER Granger's International
 Grange Close
 Clover Nook Industrial Park
 Alfreton
 Derbyshire
 DE55 4QT
 tel: +44 (0) 1773 521521
 fax: +44 (0) 1773 521262
 technical@grangers.co.uk

2 HAZARDS IDENTIFICATION

Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Harmful: may cause lung damage if swallowed.

CLASSIFICATION Xn;R65. R66, R67.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BUTANOL-norm	200-751-6	71-36-3	< 1%	R10 Xn;R22 Xi;R37/38,R41 R67
NAPHTHA (PETROLEUM) HYDROTREATED HEAVY	265-150-3	64742-48-9	60-100%	Xn;R65. R66,R67,R10.
ZIRCONIUM BUTANOLATE	213-995-3	1071-76-7	< 1%	Xi;R37/38,R41. R10,R43.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INHALATION

Move the exposed person to fresh air at once. Get medical attention. Provide rest, warmth and fresh air. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

INGESTION

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Drink plenty of water. Get medical attention immediately! Provide rest, warmth and fresh air.

SKIN CONTACT

Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

FABSIL GOLD

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
BUTANOL-norm	WEL			50 ppm(Sk)	154 mg/m3(Sk)	

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Wear approved safety goggles.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid contact with acids and oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

INHALATION

Prolonged inhalation of high concentrations may damage respiratory system.

INGESTION

Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

FABSIL GOLD

SKIN CONTACT

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Prolonged or repeated exposure may cause severe irritation.

EYE CONTACT

May cause severe irritation to eyes.

TARGET ORGANS

Skin. Eyes. Respiratory system, lungs.

12 ECOLOGICAL INFORMATION

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



PROPER SHIPPING NAME	TURPENTINE SUBSTITUTE (White Spirit)		
UN NO. ROAD	1300	ADR CLASS NO.	3
ADR CLASS	Class 3: Flammable liquids.	ADR PACK GROUP	31°(c)
HAZARD No. (ADR)	30	ADR LABEL NO.	3
HAZCHEM CODE	3Y	CEFIC TEC(R) NO.	30G30
RID CLASS NO.	3	RID PACK GROUP	31°(c)
UN NO. SEA	1300	IMDG CLASS	3.3
IMDG PAGE NO.	3375	IMDG PACK GR.	III
EMS	3-07	MFAG	311
MARINE POLLUTANT		UN NO. AIR	1300



AIR CLASS	3	AIR PACK GR.	III
-----------	---	--------------	-----

15 REGULATORY INFORMATION

LABELLING



Harmful

CONTAINS

NAPHTHA (PETROLEUM) HYDROTREATED HEAVY

RISK PHRASES

R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S2	Keep out of the reach of children
S13	Keep away from food, drink and animal feeding stuffs.

FABSIL GOLD

S23	Do not breathe vapour/spray.
S37	Wear suitable gloves.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S56	Dispose of this material and its container to hazardous or special waste collection point.
P14	Contains ZIRCONIUM BUTANOLATE. May produce an allergic reaction.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16 OTHER INFORMATION

REVISION DATE 05/03/2010

REV. NO./REPL. SDS GENERATED 1

RISK PHRASES IN FULL

R10	Flammable.
R22	Harmful if swallowed.
R37/38	Irritating to respiratory system and skin.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.