

SAFETY DATA SHEET

SPRAY WAX

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME SPRAY WAX
PRODUCT NO. A0748
SUPPLIER GRANGERS INTERNATIONAL
 GRANGE CLOSE
 CLOVER NOOK INDUSTRIAL
 ESTATE
 ALFRETON
 DERBYSHIRE
 DE55 4QT
 TEL 01773 521 521
 FAX 01773 521 262

2 HAZARDS IDENTIFICATION

Extremely flammable. Repeated exposure may cause skin dryness or cracking.

CLASSIFICATION F+;R12. R66.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	265-149-8	64742-47-8	30-60%	Xn;R65. R66.
HYDROCARBON PROPELLANT	270-704-2	68476-85-7	30-60%	F+;R12.

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Aerosol propelled by liquefied petroleum gas.

4 FIRST-AID MEASURES

INHALATION

If inhalation of vapours causes irritation or drowsiness, remove to fresh air. Get medical attention if any discomfort continues.

INGESTION

Rinse mouth thoroughly. Get medical attention if any discomfort continues.

SKIN CONTACT

Promptly flush contaminated skin with soap or mild detergent and water. Promptly remove clothing if penetrated and flush the skin with water. Get medical attention if any discomfort continues.

EYE CONTACT

Rinse the eye with water immediately. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Foam, carbon dioxide or dry powder.

SPECIAL FIRE FIGHTING PROCEDURES

Breathing apparatus should be worn if exposure to fumes is likely. Use water to keep fire exposed containers cool and disperse vapours.

UNUSUAL FIRE & EXPLOSION HAZARDS

Possible risk of can rupture when exposed to fire\high temps. Contents of aerosol will add to fuelling of fire. Solvent vapours may form explosive mixtures with air.

6 ACCIDENTAL RELEASE MEASURES

SPRAY WAX

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb material from ruptured or leaking containers onto an inert material. Transfer to suitable container for subsequent disposal.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. CAUTION. Pressurised container. Do not expose to temperatures exceeding 50°C Do not puncture or incinerate even when empty. Do not spray onto naked flame or incandescent material. Avoid contact with skin and eyes. Provide good ventilation.

STORAGE PRECAUTIONS

Store in a cool dry place away from all sources of heat including direct sunlight.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	WEL		1000 mg/m ³			
HYDROCARBON PROPELLANT	WEL	600 ppm	1430 mg/m ³	750 ppm	1780 mg/m ³	

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Aerosol

10 STABILITY AND REACTIVITY

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

MATERIALS TO AVOID

Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire or high temperatures create: Carbon dioxide (CO₂). Carbon monoxide (CO).

11 TOXICOLOGICAL INFORMATION

SKIN CONTACT

May cause sensitisation by skin contact. Prolonged contact may cause dryness of the skin.

EYE CONTACT

May cause temporary eye irritation.

HEALTH WARNINGS

INHALATION:High concentrations of vapour may cause dizziness, nausea, EYE CONTACT:May cause mild irritation or discomfort

INGESTION:May cause irritation to mouth, respiratory tract and intestinal system.

12 ECOLOGICAL INFORMATION

SPRAY WAX

ECOTOXICITY

Not classified as dangerous to the environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Do not puncture or incinerate even when empty. Dispose of in accordance with local authority requirements.

14 TRANSPORT INFORMATION

PROPER SHIPPING NAME	AEROSOL DISPENSER		
PROPER SHIPPING NAME	AEROSOL DISPENSER		
UN NO. ROAD	1950	ADR CLASS	Class 2.1: Flammable gases.
UN NO. SEA	1950	UN NO. AIR	1950

15 REGULATORY INFORMATION

LABELLING



Extremely Flammable

RISK PHRASES

R12	Extremely flammable.
R66	Repeated exposure may cause skin dryness or cracking.

SAFETY PHRASES

S2	Keep out of the reach of children
S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S37	Wear suitable gloves.
S51	Use only in well-ventilated areas.
S23	Do not breathe vapour/spray.
S35	This material and its container must be disposed of in a safe way.

16 OTHER INFORMATION

REVISION DATE 26/1/10

DATE 11/9/08

RISK PHRASES IN FULL

R12	Extremely flammable.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.