

## SAFETY DATA SHEET

### FOOTWEAR PROOFER WITH CONDITIONER AEROSOL

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME FOOTWEAR PROOFER WITH CONDITIONER AEROSOL

PRODUCT NO. GRF02

SUPPLIER Granger's International  
Grange Close  
Clover Nook Industrial Park  
Alfreton  
Derbyshire  
DE55 4QT  
tel: +44 (0) 1773 521521  
fax: +44 (0) 1773 521262  
technical@grangers.co.uk

#### 2 HAZARDS IDENTIFICATION

Extremely flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

CLASSIFICATION F+;R12. R66, R67.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BUTANE	203-448-7	106-97-8	30-60%	F+;R12
BUTANOL-norm	200-751-6	71-36-3	< 1%	R10 Xn;R22 Xi;R37/38,R41 R67
NAPHTHA (PETROLEUM) HYDROTREATED HEAVY	265-150-3	64742-48-9	30-60%	Xn;R65. R66,R67,R10.
ZIRCONIUM BUTANOLATE	213-995-3	1071-76-7	< 1%	Xi;R37/38,R41. R10,R43.

The Full Text for all R-Phrases are Displayed in Section 16

#### 4 FIRST-AID MEASURES

##### INHALATION

If inhalation of vapours causes irritation or drowsiness, remove to fresh air. Get medical attention if discomfort continues

##### INGESTION

Immediately rinse mouth and provide fresh air. Get medical attention.

##### SKIN CONTACT

Promptly flush with plenty of water if molten chemical gets on the skin or non-impervious clothing. Get medical attention immediately.

##### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids.

Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

#### 5 FIRE-FIGHTING MEASURES

##### EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc.

##### SPECIAL FIRE FIGHTING PROCEDURES

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

NOTE! Use air-supplied respirators to protect against gases/fumes.

##### UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire.

#### 6 ACCIDENTAL RELEASE MEASURES

##### SPILL CLEAN UP METHODS

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

#### 7 HANDLING AND STORAGE

**FOOTWEAR PROOFER WITH CONDITIONER AEROSOL**

**USAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

**STORAGE PRECAUTIONS**

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3	
BUTANOL-norm	WEL			50 ppm(Sk)	154 mg/m3(Sk)	

WEL = Workplace Exposure Limit.

**INGREDIENT COMMENTS**

WEL = Workplace Exposure Limits

**PROTECTIVE EQUIPMENT**



**ENGINEERING MEASURES**

Provide adequate general and local exhaust ventilation.

**RESPIRATORY EQUIPMENT**

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

**HAND PROTECTION**

Use protective gloves.

**EYE PROTECTION**

Use eye protection.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

**HYGIENE MEASURES**

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

**APPEARANCE**

Aerosol

**10 STABILITY AND REACTIVITY**

**STABILITY**

Stable under normal temperature conditions.

**CONDITIONS TO AVOID**

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

**11 TOXICOLOGICAL INFORMATION**

**INHALATION**

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

**SKIN CONTACT**

Product has a defatting effect on skin. May cause skin irritation/eczema

**FOOTWEAR PROOFER WITH CONDITIONER AEROSOL**

EYE CONTACT

Irritating to eyes.

ROUTE OF ENTRY

Inhalation.

**12 ECOLOGICAL INFORMATION**

ECOTOXICITY

Not regarded as dangerous for the environment.

**13 DISPOSAL CONSIDERATIONS**

DISPOSAL METHODS

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION**



PROPER SHIPPING NAME	AEROSOLS		
UN NO. ROAD	1950	ADR CLASS NO.	2.1
ADR CLASS	Class 2.1: Flammable gases.	ADR PACK GROUP	5°F
ADR LABEL NO.	3	HAZCHEM CODE	N/A
CEFIC TEC(R) NO.	20G53	RID CLASS NO.	2.1
RID PACK GROUP	5°F	UN NO. SEA	1950
IMDG CLASS	2.1	IMDG PACK GR.	N/A
EMS	2-13	MFAG	See Subsection 4.2 of MFAG.
UN NO. AIR	1950	AIR CLASS	2.1
AIR SUB CLASS	N/A	AIR PACK GR.	N/A

**15 REGULATORY INFORMATION**

LABELLING



Extremely Flammable

RISK PHRASES

R12	Extremely flammable.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S2	Keep out of the reach of children
S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S37	Wear suitable gloves.
S51	Use only in well-ventilated areas.
P14	Contains ZIRCONIUM BUTANOLATE. May produce an allergic reaction.
A1	Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

## FOOTWEAR PROOFER WITH CONDITIONER AEROSOL

A2

Do not spray on a naked flame or any incandescent material.

### APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

### GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

## 16 OTHER INFORMATION

REVISION DATE 05/03/2010

REV. NO./REPL. SDS GENERATED 1

### RISK PHRASES IN FULL

R10	Flammable.
R12	Extremely flammable.
R22	Harmful if swallowed.
R37/38	Irritating to respiratory system and skin.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.